



# Product Chart

## Reinforcing Steel










**SEISMIC®**  
A PACIFIC STEEL PRODUCT

# Product Chart

## For Reinforcing Steel | AS/NZS 4671

**DON'T TAKE A RISK - Specify and insist on using Pacific Steel product in your next project.**

AS/NZS Codes	Market Grade	Grade Description	Bar Diameters Available (mm)	Length Range	Specify
R300E	R	G300E Plain Bar	12, 16, 20, 25	6m - 18m	SEISMIC® 300E plain bar/coil
		G300E Plain Coil	6, 8, 10, 12, 16		
		<b>Bar Markings</b>			
D300E	D 4-Rib	G300E Deformed Bar	12, 16,	6m - 18m	SEISMIC® 300E deformed bar/coil
		G300E Deformed Coil	10, 12, 16		
		<b>Bar Markings</b>			
D300E	D 2-Rib	G300E Deformed Bar	20, 25, 32	6m - 18m	SEISMIC® 300E deformed bar
		G300E Deformed Coil	10, 12, 16		
		<b>Bar Markings</b>			
R500E	HR	G500E Plain Bar	12, 16, 20	6m - 18m	SEISMIC® 500E Micro Alloyed plain bar/coil/ ductile rod
		G500E Plain Coil (Rod for Mesh)	5.5, 6.1, 7.0, 7.5, 8.0, 9.0	Ductile Rod	
		G500E Plain Coil (Reo)	10, 12, 16	Reinforcing Coil	
		<b>Bar Markings</b>			
D500E	H 4-Rib	G500E Deformed Bar	12, 16,	6m - 18m	SEISMIC® 500E Micro Alloyed deformed bar/coil
		G500E Deformed Coil	10, 12, 16		
		<b>Bar Markings</b>			
D500E	H 2-Rib	G500E Deformed Bar	20, 25, 32, 40, 50	6m - 18m	SEISMIC® 500E Micro Alloyed deformed bar
		G500E Deformed Coil	10, 12, 16		
		<b>Bar Markings</b>			
D500E	RB	Reid Threaded Bar	12, 16, 20, 25, 32	6m - 18m	SEISMIC® 500E Micro Alloyed REIDBAR™
		G500E Deformed Bar	10, 12, 16		
		<b>Bar Markings</b>			

### Bar Lengths:

- » Bars are available in standard 1m increments between the indicated ranges e.g. 7m, 8m etc.
- » On inquiry, lengths less than 1m increments may be produced e.g. 9.2m, 12.5m, etc (further t&c's apply).

### Coil Products:

- » All coils are approximately 1.45 tonnes.

### Bar Lengths by Location:

- » Auckland – standard lengths are 6m-18m. Bars 19m-21m may be arranged (further t&c's apply).
- » Other locations – standard lengths are 6m - 15m. Bars 16m - 21m may be arranged (further t&c's apply).

All products are subject to mill confirmation & Pacific Steel terms of sale apply (visit [pacificsteel.co.nz](http://pacificsteel.co.nz))

If you would like to know more email [info@pacificsteel.co.nz](mailto:info@pacificsteel.co.nz), call 0800 722 78335 or visit [pacificsteel.co.nz](http://pacificsteel.co.nz)

E-class steel is compliant with AS/NZS 4671 requirements - such compliance can be evident by downloading our test certificates via our website [pacificsteel.co.nz](http://pacificsteel.co.nz)  
Copyright© August 2022 Pacific Steel (NZ) Limited.

